

# Single/multipair, armoured

<b>Geleiders</b>	Extension grade solid conductors Single pair 1.3mm, multipair 0.8mm
<b>Isolation</b>	Polyethylene (XLPE) 0.4mm
<b>Pairs</b>	2 cores twisted into pairs
<b>Identification</b>	Numbered for multipair
<b>Shielding*</b>	Polyester foli, polyester/aluminium foil, solid drain wire 0.6mm, polyester foil
<b>No. of pairs*</b>	1,2,3,6,8,12,16 or 24 pairs
<b>Binnenmantel</b>	Polyethylene (PE)
<b>Armering</b>	Braiding of galvanized steelwires
<b>Outer sheath</b>	PVC Flame retardant
<b>Calibration*</b>	K,T,J,E,R,S or N
<b>Nauwkeurigheid</b>	IEC-584/ ANSI MC 96.1
<b>Colour code*</b>	IEC-584/ ANSI MC 96.1
<b>Communication wire</b>	0.5mm <sup>2</sup> (7x0.31mm) copper, orange XLPE insulation multicore cables only

## Dimensions and weight

Outer diameter	10	12	14	17	18	20	22	26	mm
Weight	155	190	265	345	415	508	605	770	kg/km

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

E 85