

E55 RVS gepantserde PTFE thermokoppel verlengkabel -60°C tot 260°C

Specificaties

Aantal paren	Een of twee paar
Isolatiemateriaal	Elke draad PTFE geïsoleerd
Binnenmantel	Gevlochten glasvezel
Uitwendige armering	RVS armering 0.3 mm
Vorm	Rond
Vochtbestendigheid	Redelijk
Vlambestendigheid	Uitstekend
Temperatuurgrenzen	-60°C / +230°C continue, 260°C piek

Geleiders

Geleider uitvoering	Soepel
Aderdikte	0.5 mm ² (16x0.2 mm)

Kalibratie

Thermokoppel type	K, T, J, E, U, L, N, B, R of S
Foutgrenzen	Voldoet aan IEC 584 en ANSI MC 96,1

Kleurcode

Volgens thermokoppel kalibratie IEC 584 of ANSI MC96.1

Toepassingen

Plastic industrie, R&D, Testing, Chip machines

Afmetingen

Outside diameter	4.6	4.9	mm
Weight	39	62	kg/km



International Thermocouple Colour Codes						
Thermocouple Extension Type	ANSI	BS	DIN	NFC	JIS	IEC
JX + Iron - Constantan						
KX + Chromel - Alumel						
TX + Copper - Constantan						
EX + Chromel - Constantan						
NX + Nicrosil - Nisil						
SX + Copper RX - Alloy 11						
BX + Copper-S - Copper-E						

thermo-electra
temperature sensor solutions

Weteringweg 10, 2641 KM Pijnacker, The Netherlands
Phone: +31 15 362 12 00, E-mail: mail@thermo.nl
www.thermo-electra.com

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	E 55			
Kalibratie				
Aantal paren				
Kleurcode (IEC / ANSI)				

H8-1 Rev. 07/07