

E75 Gearmeerde thermokoppel verlengkabel -30°C tot 85°C

Specificaties

Isolatiemateriaal	Draadisolatie, hoge kwaliteit geëxtrudeerd PVC
Elektrische scherm	Twee lagen van aluminium mylar tape met aarde draad
Binnenmantel	PVC
Armering	Verzinkt staaldraad gevlecht (SWB) 0.3mm
Buitenmantel	Hoge kwaliteit geëxtrudeerd PVC
Vorm	Rond
Vochtbestendigheid	Goed
Vlambestendigheid	Goed
Mechanische sterkte	Uitstekend
Temperatuurgrenzen	-30/+85°C

Geleiders

Geleider uitvoering	A) Massief of B) Litze
Aderdikte	Massief 1.3 mm Litze 1.5 mm ² (48x0.2 mm)

Kalibratie

Thermokoppel type	K, T, J, E, U, L, N, B, R of S
Nauwkeurigheid	Voldoet aan IEC 584 en ANSI MC 96.1

Kleurcode

Volgens thermokoppel kalibratie

Afmetingen

Outside diameter	9.8	11	mm
Weight	140	150	kg/km

International Thermocouple Colour Codes						
Thermocouple Extension Type	ANSI	BS	DIN	NFC	JIS	IEC
JX + Iron - Constantan						
KX + Chromel - Alumel						
TX + Copper - Constantan						
EX + Chromel - Constantan						
NX + Nicrosil - Nisil						
SX + Copper RX - Alloy 11						
BX + Copper-S - Copper-E						

thermo-electra
temperature sensor solutions

Weteringweg 10, 2641 KM Pijnacker, The Netherlands
Phone: +31 15 362 12 00, E-mail: mail@thermo.nl
www.thermo-electra.com

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	E 75			
Conductor type (A or B)				
Kalibratie				
Colourcode (IEC / ANSI)				

