

Insulation rods made of Alsint 99.7 or Pythagoras are used to insulate inserted thermal wires. In accordance with DIN 43725, Pythagoras insulation rods can be heated to temperatures up to 2732°F/1500°C. For higher temperatures, we recommend Alsint 99.7 insulation rods.

ALSINT 99.7 TYPE C 799						PYTHAGORAS TYPE C 610					
2-bore rods			4-bore rods			2-bore rods			4-bore rods		
											
* O Ø/B Ø	O Ø/B Ø	O Ø/B Ø	* O Ø/B Ø	O Ø/B Ø	O Ø/B Ø	* O Ø/B Ø	O Ø/B Ø	O Ø/B Ø	* O Ø/B Ø	O Ø/B Ø	O Ø/B Ø
1.2 0.2	5.2 0.2	7.9 1.8	1.5 0.3	5.5 1.3	10.0 1.8	1.1 0.3	5.1 1.5	8.5 2.5	1.5 0.3	4.9 1.1	8.7 2.2
1.2 0.3	5.2 1.6	8.0 2.0	1.7 0.4	5.6 1.0	10.0 3.1	1.2 0.2	5.1 1.9	8.7 2.3	1.7 0.4	4.9 1.4	8.8 2.5
1.4 0.3	5.2 1.7	8.2 1.8	2.3 0.5	5.6 1.3	10.2 2.7	1.2 0.3	5.2 1.7	9.0 2.0	2.1 0.5	5.1 1.2	9.1 2.5
1.7 0.3	5.2 1.8	8.2 2.5	2.4 0.5	5.6 1.5	10.3 2.3	1.4 0.3	5.2 1.9	9.1 2.4	2.3 0.5	5.2 1.1	9.2 2.1
1.9 0.6	5.4 1.3	8.3 1.6	2.4 0.6	5.7 1.2	10.5 1.1	1.5 0.4	5.4 1.8	9.2 2.8	2.3 0.6	5.2 1.3	9.3 2.8