

TE1060C Keramische thermokoppel stekker tot 650°C

Toepassing

Connector	Thermokoppel en Pt100 circuits
Contacten	Zorgen voor een goed contact, zelfs in veeleisende toepassingen
Materialen	Keramiek met originele thermokoppel materiaal pinnen

Temperatuurbereik

Temperatuurgrens	Maximum 650°C.
------------------	----------------

Constructie

Body	High purity alumina body materiaal
Ontwerp	Cover met schroefjes
Gegoten isolatieschotten	Voorkomen kortsluiting

Draad afmeting

Accepteert draden	van 0,2 mm. tot 2,0 mm.
Kabel diameter	Maximum 8,0 mm.

Kleurcode

Beschikbare kleuren	Alleen wit, kleur dot voor tc kalibratie aanduiding
---------------------	---




Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

** For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors*

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model



Type J, T, K, N, E, S, R, Cu of C

IEC of ANSI

H9-1 Rev.0 7/07