

TE1210DC Ultra hoge temperatuur keramische dubbele mini jack tot 650°C

Toepassing

Connector	Thermokoppel en Pt100 circuits
Ontwerp	Geschikt voor kleine draden en minmal aderisolatie
Materialen	Ceramic body with original thermocouple material contacts

Temperatuurbereik

Temperatuurgrens	Maximum 650°C.
------------------	----------------

Constructie

Body	High purity alumina body material
Ontwerp	Robuust op lichaam ontwerp
Gegoten isolatieschotten	Voorkomen kortsluiting

Draad afmeting

Accepteert draden	Vanaf 0002 mm. tot 0,6 mm
Kabelmantel diameter	Maximaal 4,5 mm.

Accessoires

Kleurcode

Beschikbare kleuren	White only, thermocouple calibration by color dot
---------------------	---



Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

** For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors*

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE1210DC	Kalibratie	
----------	------------	--

Type J, T, K, N, E, S, R, Cu of C

IEC of ANSI

H9-1 Rev.0 7/07