

TE1134 Standaard strippaneel 3-polig

Derde contact	Derde contact is koper t.b.v. grounding/aarde
Toepassing	
Contacten	Verende 3-polige contacten, derde contact voor aarde, afscherming of 3-draads RTD
Aantal schakelingen	
Schakelingen	Beschikbaar 2 tot 12 schakelingen
Temperatuurbereik	
Temperatuurgrens	Maximaal 205°C (260°C piek)
Hoge temperatuur versie "H"	Maximum 425°C (540°C piek)
Constructie	
Body	Glasgevuld thermoplastisch materiaal
Ontwerp	Solid enkel stuk, T-moer bevestigd paneel aan de voorkant
Codering	Krasbestendige nummering
Afmetingen	
Hoogte	57,2mm
Breedte	19mm x aantal schakelingen
Kleurcode	



Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

** For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors*

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1134